

**LED-220-MR16-4W-3000K  
AC220-240V, 4w, warm white**



Input Voltage : 220V  
Frequency : 50/60Hz  
Base : GX5.3  
CCT : 3000K  
Beam Angle : 36°  
System Power : 4W  
Power Factor : >0.5  
Lumen : 190Lm  
CRI : >70

**MLQ-5W-MW  
AC220-240V, 5w, cool daylight**



Dimensions: Φ91\*60mm  
Cutout: Φ80mm  
Power: 5W / Power Factor: 0.7  
Beam Angle: 24°/40°  
Chip Quantity: 4 ,  
Power (W) : 5  
Voltage (V) : 220-240  
C R I : >85  
CCT (K) : 4000 , Lumen : 250  
Beam Angle : 24°/40°  
Color : White

**MTD0700412 3000K HM Series  
AC220-240V, 9w, warm white 4" size**



Dimensions: Φ130\*72mm  
Cutout: Φ120mm  
Power: 9W / Power Factor: 0.7  
Chip Quantity: 16 ,  
Power (W) : 9  
CCT (K) : 3000  
C R I : ≥80  
Beam Angle : 75°  
Voltage (V) : 220-240  
Lumen : 750

**MTD0700612 5700K HM Series  
AC220-240V, 14w, daylight 6" size**



Dimensions: Φ185\*94mm / Cutout:  
Φ175mm  
Power: 14W / Power Factor: 0.8  
Chip Quantity: 27 ,  
Power (W) : 14  
CCT (K) : 5700  
C R I : ≥80  
Beam Angle : 75°  
Voltage (V) : 220-240  
Lumen : 1200

**MTD0700612 3000K HM Series  
AC220-240V, 14w, warm white 6" size**



Dimensions: Φ185\*94mm / Cutout:  
Φ175mm  
Power: 14W / Power Factor: 0.8  
Chip Quantity: 27 ,  
Power (W) : 14  
CCT (K) : 3000  
C R I : ≥80  
Beam Angle : 75°  
Voltage (V) : 220-240  
Lumen : 1200

**MTD0700812/01 3000K HM Series  
AC220-240V, 42w, warm white 8" size**



Dimensions: Φ220\*116 / Cutout:  
Φ210mm  
Power: 42W / Power Factor: 0.95  
Chip Quantity: 80 ,  
Power (W) : 42  
CCT (K) : 3000  
C R I : ≥80  
Beam Angle : 75°  
Voltage (V) : 220-240  
Lumen : 3800

**MTD0700812 3000K HM Series  
AC220-240V, 29w, warm white 8" size**



Dimensions: Φ220\*116 / Cutout:  
Φ210mm  
Power: 29W / Power Factor: 0.95  
Chip Quantity: 54 ,  
Power (W) : 29  
CCT (K) : 3000  
C R I : ≥80  
Beam Angle : 75°  
Voltage (V) : 220-240  
Lumen : 2500

**MTD0700612/06 3000K HZ Series  
AC220-240V, 6", 13w, warm white**



Dimensions: Φ190\*82mm / Cutout:  
Φ172mm  
Power: 13W / Power Factor: 0.8  
Chip Quantity: 25 ,  
Power (W) : 13  
CCT (K) : 3000  
C R I : up to 80  
Beam Angle : 108°  
Voltage (V) : 220-240  
Lumen : 900