

**LED-220-MR16-4W-3000K
AC220-240V, 4w, warm white**



Input Voltage : 220V
Frequency : 50/60Hz
Base : GX5.3
CCT : 3000K
Beam Angle : 36°
System Power : 4W
Power Factor : >0.5
Lumen : 190Lm
CRI : >70

**MLQ-5W-MW
AC220-240V, 5w, cool daylight**



Dimensions: Φ91*60mm
Cutout: Φ80mm
Power: 5W / Power Factor: 0.7
Beam Angle: 24°/40°
Chip Quantity: 4 ,
Power (W) : 5
Voltage (V) : 220-240
C R I : >85
CCT (K) : 4000 , Lumen : 250
Beam Angle : 24°/40°
Color : White

**MTD0700412 3000K HM Series
AC220-240V, 9w, warm white 4" size**



Dimensions: Φ130*72mm
Cutout: Φ120mm
Power: 9W / Power Factor: 0.7
Chip Quantity: 16 ,
Power (W) : 9
CCT (K) : 3000
C R I : ≥80
Beam Angle : 75°
Voltage (V) : 220-240
Lumen : 750

**MTD0700612 5700K HM Series
AC220-240V, 14w, daylight 6" size**



Dimensions: Φ185*94mm / Cutout:
Φ175mm
Power: 14W / Power Factor: 0.8
Chip Quantity: 27 ,
Power (W) : 14
CCT (K) : 5700
C R I : ≥80
Beam Angle : 75°
Voltage (V) : 220-240
Lumen : 1200

**MTD0700612 3000K HM Series
AC220-240V, 14w, warm white 6" size**



Dimensions: Φ185*94mm / Cutout:
Φ175mm
Power: 14W / Power Factor: 0.8
Chip Quantity: 27 ,
Power (W) : 14
CCT (K) : 3000
C R I : ≥80
Beam Angle : 75°
Voltage (V) : 220-240
Lumen : 1200

**MTD0700812/01 3000K HM Series
AC220-240V, 42w, warm white 8" size**



Dimensions: Φ220*116 / Cutout:
Φ210mm
Power: 42W / Power Factor: 0.95
Chip Quantity: 80 ,
Power (W) : 42
CCT (K) : 3000
C R I : ≥80
Beam Angle : 75°
Voltage (V) : 220-240
Lumen : 3800

**MTD0700812 3000K HM Series
AC220-240V, 29w, warm white 8" size**



Dimensions: Φ220*116 / Cutout:
Φ210mm
Power: 29W / Power Factor: 0.95
Chip Quantity: 54 ,
Power (W) : 29
CCT (K) : 3000
C R I : ≥80
Beam Angle : 75°
Voltage (V) : 220-240
Lumen : 2500

**MTD0700612/06 3000K HZ Series
AC220-240V, 6", 13w, warm white**



Dimensions: Φ190*82mm / Cutout:
Φ172mm
Power: 13W / Power Factor: 0.8
Chip Quantity: 25 ,
Power (W) : 13
CCT (K) : 3000
C R I : up to 80
Beam Angle : 108°
Voltage (V) : 220-240
Lumen : 900